

ATF MULTI LV

TRANSMISSIONS WITH 6 OR MORE SPEEDS



APRIL ATF MULTI LV is a superior quality 100% synthetic low viscosity automatic transmission fluid made with APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for transmissions with 6 or more speeds as well as hydraulic and power steering systems.

SPECIFICATIONS: Aisin-Warner AW-1, T-IV, JWS 3309/3324; Allison C-3/4; American Motors ATF +3/+4; BMW ATF 3+, P/N 81-22-9-407-858/859, P/N 83-22-0-024-359, P/N 83-22-0-026-922, P/N 83-22-0-142-156/516, P/N 83-22-0-397-114, P/N 83-22-0-402-413, P/N 83-22-0-403-674, P/N 83-22-2-152-426, P/N 83-22-2-163-514, P/N 83-22-2-289-720, P/N 83-22-2-305-397, P/N 83-22-9-407-765/807; Castrol Transmax J; Chrysler ATF +3 (MS-7176-E), ATF +4 (MS-9602), P/N 05127382AA/AB, P/N 05189966AB, P/N 68043742AA/AB, P/N 68157995AA, P/N 68171866AB, P/N 68218925AA, P/N 68333587AA; Esso LT 71141; Ford Mercon V/LV/SP/ULV; GM Dexron II/IIID/IIIE/IIII/IIIG/IIIH/VI/HP/ULV, P/N 12378515, P/N 88863400/401; Honda DW-1, ATF Type 3.0/3.1/Z1; Hyundai/Kia NWS-9638 T-5, RED-1, SP-II/III/IV/IV-RR, SPH-IV, 040000C90SG; Idemitsu ATF HP, K17; Jaguar Fluid 8432, ATF 3403 M115, ATF M-1375.4, LT71141; Jaso M315-2013 1A; Jatco 3100 PL085; Land Rover P/N TYK500050, LR0022460: LV; Maserati 231603; Mazda FW 6A EL, FW 6AX EL, FZ, M-III, M-V; Mercedes MB 236.5/6/7/8/9/10/11/12/14/15/17/18/41; Mitsubishi SP II/III/IV, DiaQueen ATF PA/J2/J3; Mobil ATF 3309/3317; Nissan Matic D/J/K/P/S; Pennzoil Platinum LV; Porsche ATF 3403-M115, P/N 000-043-304-00; Saab 93 165 147-AW-1; Shell ATF 134/134 FE/3353/3403, LA2634, M-1375.4, M-L12108; Subaru ATF, ATF-HP; Texaco ETL-7045E/8072B, N402; Toyota ATF FZ/WS/T-IV; Valvoline MaxLife; Volvo T-IV; VW G-053-001-A2, P/N G-052-025-A2, P/N G-052-533, P/N G-052-990-A2, P/N G-055-005-A/A2, P/N G-055-025-A2, P/N G-055-540-A2, P/N G-060-162-A1/A2/A6; ZF TE-ML 02F/03D/04D/ 05L/09/11A/11B/14A/14B/16L/17C, Lifeguardfluid 5/6/8/9

FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-ATFMLV
5 litres	3 x 5 L	15-ATFMLV
pail	18.9 L	18.9-ATFMLV
keg	60 L	77-ATFMLV
drum	205 L	205-ATFMLV
tote	1,000 L	900-ATFMLV
bulk	bulk	100-ATFMLV

PROPERTY	METHOD	VALUE
color	ASTM D1500	6.5
density @ 15 °C (kg/l)	ASTM D4052	0.8417
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	29.63
kinematic viscosity @ 100 °C (cSt)	ASTM D445	6.10
viscosity index	ASTM D2270	160
flash point (°C)	ASTM D92	220
pour point (°C)	ASTM D97	-51
copper corrosion	ASTM D130	1A

