

CVT FLUID



APRIL CVT FLUID is a superior quality 100% synthetic transmission fluid made with APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for CVT (Continuously Variable Transmission) and single-speed transmissions used in BEV (Battery Electric Vehicles).

SPECIFICATIONS: **Audi** Multitronic; **Chery** CVT, WCF-1; **Chrysler/Dodge/Jeep/Mopar** CVT+4, NS-2; **Citroen** PSA Standard 9735EF; **Daihatsu** AMMIX CVT Fluid DC/DFC, Fluid TC; **Fiat** Tutela CVT N.G.; **Ford** WSD-M2C-199A, Escape Hybrid Ecvt; **Fujijyuuko** i-CVTF FG; **GM** CVTF I-Green2, DEX-CVT, HP-CVT, VT40, 1940713/4; **Honda** CVT, e:HEV, HCF2, HMMF Ultra, Immd, Z-1; **Hyundai/Kia** CVT-1/J1, SPIII, SP CVT-1; **Idemitsu** CVTF-EX1; **Jatco** CVT 8 Hybrid, JR712E; **JWS** 3401; **Lexus** Fluid TC/FE; **Mazda** JWS 3320, SKYACTIVE-HYBRID; **MG** **Rover** EM-CVT; **Mini Cooper** EZL, EZL 799, EZL 799A, ZF CVT V1, 83-22-0-136-376, 83-22-0-429-154; **Mitsubishi** CVTF ECO J4, Diaqueen CVTF J1/J4/J4+/MA1, SPIII; **Nissan** Altima Hybrid, e Power, N-CVT, NS-1/2/2V/3; **Opel/Vauxhall** 7-speed CVT, 95529854; **Perodua** D-CVT; **Peugeot** PSA Standard 9735EF; **Punch** CVTF-EX1 (VT2/3/5 Transmissions); **Renault** Elf Matic CVT; **Shell** Green 1V, SL 2100; **Subaru** CV-30, CVTF, CVTF II/III, ECVT, HT CVTF, HT CVTF-LV, iCVT, iCVT FG, K0421Y0700, K0425Y0710/1; **Suzuki** CVT Green 1/1V/2, CVTF TC/3320/4401, NS-2; **Toyota** CVTF TC/FE, e-Transaxle Fluid TE, Prius, THS-II; **Volvo** CVT 4959; **VW/Audi** TL 521 16/80 (G-052-516/180); **Zotye** CVTs

| FORMAT | LITRES | CODE |
|--------|--------------|------------|
| quart | 12 x 0.946 L | 12-CVT-SF |
| keg | 60 L | 77-CVT-SF |
| drum | 205 L | 205-CVT-SF |

| PROPERTY | METHOD | VALUE |
|------------------------------------|------------|--------|
| color | ASTM D1500 | 3.0 |
| density @ 15 °C (kg/l) | ASTM D4052 | 0.8459 |
| water crackle | hot plate | dry |
| kinematic viscosity @ 40 °C (cSt) | ASTM D445 | 33.73 |
| kinematic viscosity @ 100 °C (cSt) | ASTM D445 | 7.12 |
| Brookfield viscosity @ -40 °C (cP) | ASTM D2983 | 10,000 |
| viscosity index | ASTM D2270 | 181 |
| flash point (°C) | ASTM D92 | >300 |
| pour point (°C) | ASTM D97 | -48 |
| rust protection | ASTM D665A | pass |

