

RACING

APRIL RACING 5W-50 is a superior quality 100% synthetic gasoline and diesel engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection, improved fuel economy and easy cold temperature start-up.

SPECIFICATIONS: **ACEA** A3/B3, A3/B4; **API** SN; **BMW** High Performance LL-01; **Mercedes** MB 229.3; **Porsche** A40; **VW** 505 00



GRADE	FORMAT	LITRES	CODE
5W-50	quart	12 x 0.946 L	12-HYPER5W50
	pail	18.9 L	18.9-HYPER5W50
	keg	60 L	77-HYPER5W50
	drum	205 L	205-HYPER5W50
	tote	1,000 L	900-HYPER5W50

PROPERTY	METHOD	VALUE
color	ASTM D1500	3.5
density @ 15 °C (kg/l)	ASTM D4052	0.8535
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	110.6
kinematic viscosity @ 100 °C (cSt)	ASTM D445	18.7
viscosity index	ASTM D2270	190
TBN (mg KOH/g)	ASTM D2896	7.74
flash point (°C)	ASTM D92	210
pour point (°C)	ASTM D97	-45
CCS viscosity (cP @ °C)	ASTM D5293	5,118 (-30)

