APRIL TECHNICAL DATA SHEET

2-CYCLE SNOWMOBILE OIL

APRIL 2-CYCLE SNOWMOBILE OIL is a premium quality 2-cycle gasoline engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection and performance. Suitable for pre-mix and oil injection systems, it meets the specifications of Arctic Cat, Bombardier (BRP), Polaris and Yamaha. For a 50:1 fuel/oil ratio, mix 100 ml with 5 L of gasoline.

HOMOLOGATIONS-SPECIFICATIONS: **API** TC; **JASO** FB; **NMMA** TC-W3® (licence # RL-13894W

FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-SNOW-SF
gallon	4 x 4 L	16-SNOW-SF
drum	205 L	205-SNOW-SF
tote	1,000 L	900-SNOW-SF

PROPERTY	METHOD	VALUE
color	visual	blue
density @ 15 °C (kg/l)	ASTM D4052	0.8723
kinematic viscosity @ 40 °C (cSt)	ASTM D445	61.56
kinematic viscosity @ 100 °C (cSt)	ASTM D445	9.25
Brookfield viscosity @ -25 °C (cP)	ASTM D2983	5,910
viscosity index	ASTM D2270	129
flash point (°C)	ASTM D92	95
pour point (°C)	ASTM D97	-39

APRIL NANO1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0
1 800 393-3921 info@123april.com