

# APRIL

## TECHNICAL DATA SHEET

### 4-CYCLE SMALL ENGINE OIL

**APRIL SMALL ENGINE OIL** is a premium quality gasoline engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection and performance. Available in three SAE viscosity grades, the 5W-30 is recommended for side-by-sides and all-terrain vehicles, the 10W-40 is recommended for motorcycles, scooters, side-by-sides and all-terrain vehicles, and the 20W-50 is recommended for air-cooled motorcycles.

SPECIFICATIONS: **API SN** (5W-30), SJ; **JASO MA**



GRADE	FORMAT	LITRES	CODE
5W-30	quart	12 x 0.946 L	12-5W304C-SF
	keg	60 L	77-5W304C-SF
	drum	205 L	205-5W304C-SF
	tote	1,000 L	900-5W304C-SF
10W-40	quart	12 x 0.946 L	12-10W404C-SF
	keg	60 L	77-10W404C-SF
	drum	205 L	205-10W404C-SF
	tote	1,000 L	900-10W404C-SF
20W-50	quart	12 x 0.946 L	12-20W504C-SF
	tote	1,000 L	900-20W504C-SF

PROPERTY	METHOD	VALUE		
		5W-30	10W-40	20W-50
color	visual	amber	amber	amber
kinematic viscosity @ 100 °C (cSt)	ASTM D445	11.0	14.8	19.0
flash point (°C)	ASTM D92	238	247	258
pour point (°C)	ASTM D97	-33	-33	-33
CCS viscosity (cP @ °C)	ASTM D5293	5,638 (-30)	7,000 (-25)	6,000 (-15)



**APRIL NANO1™**  
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0  
1 800 393-3921 info@123april.com