

ATF HD-T6

APRIL ATF HD-T6 is a superior quality 100% synthetic automatic transmission fluid recommended for transmissions requiring an Allison TES-668 approved fluid, as well as for applications requiring TES-468, TES-389 and TES-295.

HOMOLOGATIONS-SPECIFICATIONS: **Allison** TES-668 (approval #668-10472024), TES-468/389/295; **DTFR** 13C190, MB 236.91/92; **Ford** Mercon, WSS-M2C922-A1; **GM** Dexron II/III/IV /IIH; **JASO** 1-A; **MAN** 339-V1; **Voith** H55.6335.xx; **Volvo** 97340, 97341

FORMAT	LITRES	CODE
pail	18.9 L	18.9-ATFS668-SF
keg O	60 L	60-ATFS668-SF
drum	205 L	205-ATFS668-SF
tote	1,000 L	900-ATFS668-SF
bulk	bulk	100-ATFS668-SF

PROPERTY	METHOD	VALUE
color	visual	red
density @ 15 °C (kg/l)	ASTM D4052	0.8463
kinematic viscosity @ 40 °C (cSt)	ASTM D445	34.4
kinematic viscosity @ 100 °C (cSt)	ASTM D445	7.0
Brookfield viscosity @ -40 °C (cP)	ASTM D2983	14,100
viscosity index	ASTM D2270	170
flash point (°C)	ASTM D92	228
pour point (°C)	ASTM D97	-45



AUTHORIZED BY
ALLISON TRANSMISSION, INC.

• **TES 668®** •

COMPLIES WITH
TES 668 SPECIFICATIONS

