APRIL TECHNICAL DATA SHEET

ATF TYPE F

APRIL ATF TYPE F is a premium quality automatic transmission fluid made with APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for pre-1980 Ford vehicles requiring Ford Type F transmission fluid.

SPECIFICATIONS: **Ford** ESW M2C33-F/G

FORMAT	LITRES	CODE
pail	18.9 L	18.9-ATFF-SF
drum	205 L	205-ATFF-SF
tote	1,000 L	900-ATFF-SF
bulk	bulk	100-ATFF-SF

PROPERTY	METHOD	VALUE
color	visual	red
density @ 15 °C (kg/l)	ASTM D4052	0.8635
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	41.0
kinematic viscosity @ 100 °C (cSt)	ASTM D445	8.2
viscosity index	ASTM D2270	180
Brookfield viscosity @ -40 °C (cP)	ASTM D2983	23,300
flash point (°C)	ASTM D92	204
pour point (°C)	ASTM D97	-48

APRIL NANO1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0
1 800 393-3921 info@aprilsuperflo.com