

### CVT FLUID



**APRIL CVT FLUID** is a superior quality 100% synthetic transmission fluid made with APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for CVT (Continuously Variable Transmission) and single-speed transmissions used in BEV (Battery Electric Vehicles).

**SPECIFICATIONS:** Audi Multitronic; **BMW** ZF CVT V1, EZL 799, P/N 83-22-0-136-376/83-22-0-429-154; **Castrol** Transmax CVT; **Chrysler** NS-2, CVTF +4; **Fiat** Tutela CVT N.G.; **Ford** CVT23, CVT30, Mercon C, WSD-M2C-199A, WSS-M2C928-A, WSS-M2C933-A; **GM** DEX-CVT, HP-CVT, VT40, CVTF I-Green2, P/N 1940713/4; **Honda** CVT, HEV, iMMD, HMMF Ultra, HCF2, Z-1; **Hyundai/Kia** CVT-1/J1, SPIII; **Idemitsu** CVTF-EX1; **Jatco** Hybrid eTransmission, CVT8 Hybrid, JR712E; **Lexus** Fluid TC/FE; **Mazda** JWS 3320; **Mercedes** CVT28, MB 236.20; **Mini Cooper** EZL/EZL 799A, ZF CVT V1; **Mitsubishi** Diaqueen CVTF J1/J4/J4+, SPIII, CVTF ECO J4; **Motorcraft** XT-7-QCFT; **Nissan** NS-1/2/2V3, N-CVT; **Pennzoil** Platinum CVT-2; **Punch** CVTF-EX1; **Shell** Green 1V; **Subaru** iCVT, iCVT FG, ECVT, CVTF, CVTF-II/III, HT CVTF, HT CVTF-LV; **Suzuki** CVTF TC/3320/4401, NS-2, CVT Green 1/1V/2; **Tesla** Model S/3/X/Y; **Toyota** CVTF TC/FE, Prius; **Valvoline** CVT; **VW** P/N G-052-180/516

FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-CVT-SF
keg	60 L	77-CVT-SF
drum	205 L	205-CVT-SF

PROPERTY	METHOD	VALUE
color	ASTM D1500	3.0
density @ 15 °C (kg/l)	ASTM D4052	0.8459
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	33.73
kinematic viscosity @ 100 °C (cSt)	ASTM D445	7.12
Brookfield viscosity @ -40 °C (cP)	ASTM D2983	10,000
viscosity index	ASTM D2270	181
flash point (°C)	ASTM D92	>300
pour point (°C)	ASTM D97	-48
rust protection	ASTM D665A	pass

