

CVT FLUID

APRIL CVT FLUID is a superior quality 100% synthetic continuously variable transmission fluid made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed protection and performance.

SPECIFICATIONS: **BMW/Mini** ZF CVT V1, EZL 799, P/N 83-22-0-136-376, P/N 83-22-0-429-154; **Chrysler/Dodge/Jeep** NS-2, CVTF +4; **Daihatsu** AMMIX CVT Fluid DC/DFC/DFE; **Ford/Lincoln/Mercury** CVT23, CVT30, Mercon C, WSS-M2C928-A, WSS-M2C933-A, Motorcraft XT-7-QCFT; **GM/GMC/Buick/Chevrolet** DEX-CVT, CVTF I-Green2; **Honda/Acura** HMMF (w/o starting clutch), HCF2; **Hyundai/Kia** CVT-J1; **Idemitsu** CVTS-EX1; **Mazda** JWS 3320; **Mercedes/Daimler** CVT28, MB 236.20; **Mitsubishi** Diaqueen CVTF J1/J4/J4+; **Nissan/Infiniti** NS-1/2/3; **Pennzoil** Platinum CVT-2; **Punch** CVT; **Shell** Green 1V; **Subaru** CV-30, e-CVT, i-CVT F/FG, Lineartronic Chain CVTF/CVTF-II, Lineartronic High Torque CVTF, P/N K0425Y0710; **Suzuki** CVTF TC/3320, NS-2, CVT Green 1/1V/2; **Toyota/Lexus/Scion** CVTF TC/FE; **Valvoline** CVT; **VW/Audi** Multitronic, P/N G-052-516 (TL 521 16), P/N G-052-180 (TL 521 80)



FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-CVT-SF
keg	60 L	77-CVT-SF

PROPERTY	METHOD	VALUE
color	ASTM D1500	3.0
density @ 15 °C (kg/l)	ASTM D4052	0.8459
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	33.73
kinematic viscosity @ 100 °C (cSt)	ASTM D445	7.12
Brookfield viscosity @ -40 °C (cP)	ASTM D2983	10,000
viscosity index	ASTM D2270	181
flash point (°C)	ASTM D92	>300
pour point (°C)	ASTM D97	-48
rust protection	ASTM D665A	pass

