

ECOLO VACUUM OIL

APRIL ECOLO VACUUM OIL is a superior quality inherently biodegradable lubricant (20-60% in 28 days) made with pure virgin base oil, environmentally friendly zinc free additives and APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. It has excellent anti-oxidation and anti-corrosion properties. Recommended for rotary and sliding vane vacuum pumps operating in areas sensitive to environmental pollution, such as on or near water and aquifers, near water treatment plants, on farmland, in forests and endangered species' habitats. Available in one grade.

SPECIFICATIONS: **ISO 6743-3A-DVC**

FORMAT	LITRES	CODE
pail	18.9 L	18.9-VACECO-SF
tote	1,000 L	900-VACECO-SF

PROPERTY	METHOD	VALUE
color	visual	amber
density @ 15 °C (kg/l)	ASTM D4052	0.8752
water crackle	hot plate	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	61.10
kinematic viscosity @ 100 °C (cSt)	ASTM D445	8.08
viscosity index	ASTM D2270	99
flash point (°C)	ASTM D92	242
pour point (°C)	ASTM D97	-21
rust protection	ASTM D665A/B	pass
water protection	ASTM D1401	pass
copper protection	ASTM D130	pass
oxidation stability	ASTM D2893	pass
anti-foaming	ASTM D892	pass

