APRIL TECHNICAL DATA SHEET

EURO

VW *504 00, 507 00*

APRIL EURO 5W-30 is a superior quality 100% synthetic gasoline and diesel engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection, improved fuel economy and easy cold temperature start-up. Specially formulated for Volkswagen and Audi vehicles requiring a 504 00 or 507 00 engine oil.

SPECIFICATIONS: **ACEA** C3; **API** SP; **BMW** LL-04; **Mercedes** MB 229.51; **Porsche** C30; **VW** 504 00, 507 00

GRADE	FORMAT	LITRES	CODE
5W-30	quart	12 x 0.946 L	12-HYPER5W30VW
	5 litres	3 x 5 L	15-HYPER5W30VW
	keg	60 L	77-HYPER5W30VW
	drum	205 L	205-HYPER5W30VW
	tote	1,000 L	900-HYPER5W30VW
	bulk	bulk	100-HYPER5W30VW

PROPERTY	METHOD	VALUE
color	visual	amber
density @ 15 °C (kg/l)	ASTM D4052	0.852
kinematic viscosity @ 40 °C (cSt)	ASTM D445	69.0
kinematic viscosity @ 100 °C (cSt)	ASTM D445	11.7
CCS viscosity (cP @ °C)	ASTM D5293	5,455 (-30)
viscosity index	ASTM D2270	172
flash point (°C)	ASTM D92	210
pour point (°C)	ASTM D97	-42
TBN (mg KOH/g)	ASTM D2896	6.5

APRIL NANO1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0
1 800 393-3921 info@aprilsuperflo.com