

APRIL

TECHNICAL DATA SHEET



HD-EXTRA

APRIL HD-EXTRA is a superior quality extra tacky red lithium complex grease made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for wheel bearings, fifth wheel trailer hitches and high load transportation, heavy equipment, industrial and marine applications.

SPECIFICATIONS: **NLGI GC-LB #2**

FORMAT	Kg	CODE
cartridge	50 x 397g	50/397-HDEXTRA2
pail	17 kg	17-HDEXTRA2
keg	55 kg	55-HDEXTRA2

PROPERTY	METHOD	VALUE
color	visual	red
thickener	ASTM D128	lithium complex
dropping point (°C / °F)	ASTM D2265	260 / 500
cone penetration @ 25 °C (0.1mm)	ASTM D217	280
consistency grade	ASTM D217	2
performance grade	ASTM D4950	GC-LB
base oil kinematic viscosity @ 100 °C (cSt)	ASTM D445	39
base oil kinematic viscosity @ 40 °C (cSt)	ASTM D445	460
viscosity index	ASTM D2270	130
four ball wear (mm)	ASTM D2266	0.5
four ball EP weld point (kg)	ASTM D2596	400
load wear index	ASTM D2596	65
Timken OK load (lbs)	ASTM D2509	80
high temperature wheel bearing life (hrs)	ASTM D3527	240
leakage tendencies (g)	ASTM D4290	5
water washout (%)	ASTM D1264	10
rust protection	ASTM D1743	pass
copper corrosion	ASTM D4048	1b

