

### HM HIGH MILEAGE ENGINE OIL

**APRIL HM** is a premium quality HM (High Mileage) synthetic blend gasoline engine oil made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed engine protection and performance. Specially formulated to prevent oil leaks and extend the life of vehicles with over 120,000 km. Available in two SAE viscosity grades.

**HOMOLOGATIONS-SPECIFICATIONS:** API SP, SN PLUS, SN; **Asian OEMs:** Honda, Hyundai, Kia, Mazda, Nissan, Subaru, Toyota; **Chrysler/Dodge/Jeep/RAM** MS-6395; **Ford/Lincoln/Mercury** WSS-M2C945-B1, WSS-M2C960-A1 (5W-20); WSS-M2C946-B1, WSS-M2C961-A1 (5W-30); **GM/GMC/Buick/Chevrolet** 6094M; **ILSAC** GF-6A



GRADE	FORMAT	LITRES	CODE
5W-20	quart	12 x 0.946 L	12-BLE5W20HM-SF
	5 litres	3 x 5 L	15-BLE5W20HM-SF
5W-30	quart	12 x 0.946 L	12-BLE5W30HM-SF
	5 litres	3 x 5 L	15-BLE5W30HM-SF

PROPERTY	METHOD	VALUE	
		5W-20	5W-30
color	ASTM D1500	3	3
density @ 15 °C (kg/l)	ASTM D4052	0.8565	0.8617
water crackle	hot plate	dry	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	48.11	58.55
kinematic viscosity @ 100 °C (cSt)	ASTM D445	8.54	9.80
viscosity index	ASTM D2270	156	153
TBN (mg KOH/g)	ASTM D2896	9.3	9.3
flash point (°C)	ASTM D92	219	225
pour point (°C)	ASTM D97	-45	-45
CCS viscosity (cP @ °C)	ASTM D5293	4,413 (-30)	6,300 (-30)
NOACK (%)	ASTM D5800	13	13

