

APRIL

TECHNICAL DATA SHEET

SERIE 1

APRIL SERIE 1 is a premium quality 2-cycle diesel engine oil made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed engine protection and performance. Recommended for older model 2-cycle diesel engines and manual transmissions. Available in two SAE viscosity grades.

SPECIFICATIONS: Allison C-4; API CF-2, CF, CD-II, CD; Caterpillar TO-2; Detroit Diesel 7SE270



GRADE	FORMAT	LITRES	CODE
SAE 30	pail	18.9 L	18.9-SAE30DD-SF
	drum	205 L	205-SAE30DD-SF
	tote	1,000 L	900-SAE30DD-SF
	bulk	bulk	100-SAE30DD-SF
SAE 40	gallon	4 x 4 L	16-SAE40DD-SF
	pail	18.9 L	18.9-SAE40DD-SF
	drum	205 L	205-SAE40DD-SF
	tote	1,000 L	900-SAE40DD-SF
	bulk	bulk	100-SAE40DD-SF

PROPERTY	METHOD	VALUE	
		SAE 30	SAE 40
color	ASTM D1500	7.2	7.5
density @ 15 °C (kg/l)	ASTM D4052	0.8828	0.8841
kinematic viscosity @ 40 °C (cSt)	ASTM D445	87.87	139.25
kinematic viscosity @ 100 °C (cSt)	ASTM D445	11.10	15.23
viscosity index	ASTM D2270	113	112
TBN (mg KOH/g)	ASTM D2896	7.3	7.3
flash point (°C)	ASTM D92	236	251
pour point (°C)	ASTM D97	-21	-18
sulfated ash (% wt)	ASTM D874	0.8	0.8



APRIL NANO 1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0
1 800 393-3921 info@aprilsuperflo.com