APRIL

TECHNICAL DATA SHEET

SUPREME

APRIL SUPREME is a superior quality red lithium complex grease made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for wheel bearings and heavy duty transportation, heavy equipment and industrial applications.

SPECIFICATIONS: **NLGI** GC-LB #2

FORMAT	Kg	CODE
454 g pot	12 x 454 g	1-BEARING-SF
1.82 kg pot	6 x 1.82 kg	4-BEARING-SF

PROPERTY	METHOD	VALUE
color	visual	red
thickener	ASTM D128	lithium complex
dropping point (°C / °F)	ASTM D2265	≥260 / 500
cone penetration @ 25 °C (0.1mm)	ASTM D217	265-295
consistency grade	ASTM D217	2
shear stability, 100 000 strokes (0.1mm)	ASTM D217	30 max
performance grade	ASTM D4950	GC-LB
base oil kinematic viscosity @ 40 °C (cSt)	ASTM D445	224
base oil kinematic viscosity @ 100 °C (cSt)	ASTM D445	17.4
four ball EP weld point (kg)	ASTM D2596	400
Timken OK load (lbs)	ASTM D2509	60
rust protection	ASTM D1743	pass
water spray off (% wt)	ASTM D4049	20 max

APRIL NANO1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte (Québec) Canada G0L 1K0
1 800 393-3921, ext. 1 info@aprilsuperflo.com