



TECHNICAL DATA SHEET

2025-10-08

TC-W3 SYNTHETIC



APRIL TC-W3 is a superior quality 100% synthetic 2-cycle gasoline engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection, improved fuel economy and easy cold temperature start-up. Suitable for pre-mix and oil injection systems, it is recommended for 2-cycle water-cooled motorcycles, scooters and outboard motors. Not recommended for small air-cooled motors (chain saws, edge trimmers, leaf blowers, etc.).

HOMOLOGATIONS-SPECIFICATIONS: **API TC**; **JASO FB**; **NMMA TC-W3®** (licence # RL-13894W)

FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-SYNTCW3-SF
keg	60 L	77-SYNTCW3-SF
drum	205 L	205-SYNTCW3-SF
tote	1,000 L	900-SYNTCW3-SF

PROPERTY	METHOD	VALUE
color	visual	blue
density @ 15 °C (kg/l)	ASTM D4052	0.9522
kinematic viscosity @ 40 °C (cSt)	ASTM D445	44.6
kinematic viscosity @ 100 °C (cSt)	ASTM D445	7.9
Brookfield viscosity @ -25 °C (cP)	ASTM D2983	4,750
viscosity index	ASTM D2270	149
flash point (°C)	ASTM D92	140
pour point (°C)	ASTM D97	-42



APRIL NANO1™
LUBRICANT TECHNOLOGY

APRIL SUPER FLO 9, rue Béland, L'Isle-Verte QC Canada G0L 1K0
1 800 393-3921 info@123april.com