

TC-W3

APRIL TC-W3 is a premium quality 2-cycle gasoline engine oil made with APRIL NANO 1™ lubricant technology for unsurpassed engine protection and performance. Suitable for pre-mix and oil injection systems, it is recommended for 2-cycle water-cooled motorcycles, scooters and outboard motors. Not recommended for small air-cooled motors (chain saws, edge trimmers, leaf blowers, etc.).

HOMOLOGATIONS-SPECIFICATIONS: **API TC**; **JASO FB**; **NMMA TC-W3®** (licence # RL-13894W)



FORMAT	LITRES	CODE
quart	12 x 0.946 L	12-TCW3-SF
gallon	4 x 4 L	16-TCW3-SF
keg	60 L	77-TCW3-SF
drum	205 L	205-TCW3-SF
tote	1,000 L	900-TCW3-SF

PROPERTY	METHOD	VALUE
color	visual	blue
density @ 15 °C (kg/l)	ASTM D4052	0.8723
kinematic viscosity @ 40 °C (cSt)	ASTM D445	61.56
kinematic viscosity @ 100 °C (cSt)	ASTM D445	9.25
Brookfield viscosity @ -25 °C (cP)	ASTM D2983	5,910
viscosity index	ASTM D2270	129
flash point (°C)	ASTM D92	95
pour point (°C)	ASTM D97	-39

